

QUICK SPECIFICATIONS - CUSTOMER SUMMARY

Agency Name	Benton County Fire District #4	Date	9/15/2026
Contact Name	Ray Newton	Salesperson	Kyle Jagelski
Contact Phone	509-430-4797	Equipment Rep	N/A
Contact Email	rnewton@bcfd4.org	Project Manager	Jordan Koffler

CHASSIS

FORD F550 : INCLUDED SWEV STD
2027 FORD F550 SUPERDUTY CREW CAB. 4X4, 179" WB, 60" CA, DRW, 19,500 GVW, 6.7L POWERSTROKE DIESEL, VERMILLION RED, FIRE PREP PKG.

DRIVETRAIN / SUSPENSION

BUCKSTOP SRW CONV : WILDLAND ELECTRONIC / FORD
E-CLIK PRO SYSTEM WITH FOUR BEST IN CLASS 2.5 REMOTE RESERVOIR SHOCK ABSORBERS WITH 7/8" SHAFTS, ECU, IMU, ALL WIRING HARNESSSES, AND COLOR TOUCH-SCREEN CONTROLLER WITH A PILAR MOUNT.
16TWO CUSTOM WEIGHT-RATED PROGRESSIVE 4" LIFT REAR LEAF SPRINGS, U-BOLTS, AND NUTS.
BUCKSTOP COMPREHESIVE SUSPENSION BASE KIT - REPLACEMENT COIL SPRINGS, FABRICATED RADIUS ARMS, HD SWAY BAR, SYNERGY ADJUSTABLE TRACK BAR, HD TRACK BAR MOUNT, 2 STAGE SOFT-STOP SPRINGS, AND ASSOCIATED MOUNTS AND BRACKETS.
335/80R20 TIRES (5), & 11"X20" REVERSIBLE DOT ALUM WHEELS (5), HIGH ARCH FENDER FLARES, OUTBACK BUMPER (WIDE)

REAR DECK CONFIGURATION

STANDARD
STANDARD REAR DECK SELECTION - NO L3 COMPARTMENT, PUMP TO DS RADIATOR OUT, ALLOWS TS ACCESS AND EXPANDED SELECTIONS

HOSE REEL MODEL

TOPSIDE DUAL
DUAL HANNAY MODEL: EF4038-17-18 (LT & RT) 12V ELECTRIC REWIND HOSE REELS MOUNTED TO TOP OF BODY ON LH & RH SIDES PER CONFIGURATION. PAINTED BLACK, 1" NH OUTLET THREADS, W/ STANDARD SPOOL STYLE ROLLER ASSEMBLIES
CAPACITY: 125' 1" / 200' 3/4

L3 POSITION

L3 HEX PUNCH - STANDARD
HEX PUNCH FASTBACK ENCLOSURE GUARD INSTALLED TO L3 BODY POSITION. POWDERCOATED JOB COLOR

R3 POSITION

R3 COMPARTMENT - STANDARD
LIFT DOOR TOPSIDE COMPARTMENT INSTALLED TO R3 BODY POSITION. (32"W X 31.5"H X 18"D): VERTICAL LIFT DOOR WITH DUAL GAS SHOCKS. (2) ADJUSTABLE SHELVES, D RING HANDLE, COMPARTMENT CIRCLE VENT AND LOUVER ASSY. CTECH SINGLE ENCLOSED 6"D DRAWER INSTALLED TO BASE OF R3 COMPARTMENT FOR ADAPTER & APPLIANCE STORAGE.

TOPSIDE PRECONNECT(S)

NONE
NO TOPSIDE PRECONNECTS INSTALLED

TOPSIDE - FRONT CROSSFRAME DUNNAGE

COFFIN BOX - STANDARD
TOPSIDE FRONT COFFIN BOX INSTALLED OVER L1/R1 TRANSVERSE (48"W X 18"D X 12"H). T LATCH HANDLE ON LID SURFACE, HINGED CAB SIDE, GAS SHOCK ASSIST, POWDERCOAT BK62

TOPSIDE - LH DUNNAGE

LH: 40.5" BASKET (REEL FWD, NO L3)

TOPSIDE BASKET HEX PUNCH 40.5" X 18" X 12" PC BK62 (SMOOTH OUTER FACE TO OUTSIDE)

TOPSIDE - RH DUNNAGE

RH: 60.5" BASKET (REEL FWD, W/ R3)

TOPSIDE BASKET HEX PUNCH 60.5" X 18" X 12" PC BK62 (SMOOTH OUTER FACE TO OUTSIDE) REAR HEXES REMOVED FOR HANDLE AND LIGHT MOUNTING

INTEGRATED ANGLED HANDLE AND ENCLOSURE ON OUTSIDE

PUMP CONTROL SYSTEM

SWEV INTERNAL CONTROL DUAL PANELS (21H)

INTERNAL FAB ELECTRIC ACTUATED DUAL CONTROL SYSTEM FOR DARLEY 21H, ACTUATOR BOX & LINEAR ACTUATORS, TOGGLE SWITCHES FOR THROTTLE & CHOKE, REUSE, TINY TACH, -30, 0-300 GAUGE, RUN / STOP IGN SWITCH, PANEL LIGHT, IN CAB PUMP PANEL FABRICATED W/ ETCHED LABELING - MIRRORS MAIN PANEL FUNCTIONALITY

FOAM SYSTEM

TRIDENT ATP

TRIDENT FOAMATE 1.0 CLASS A ATP FOAM SYSTEM

BRASS HOUSING, PROPORTIONER STYLE - MOUNTED TO PLUMBING STEP FACE OR TO PUMP CONTROL AREA

INLINE 1/4 TURN VALVES FOR FOAM TANK DRAIN AND FOAM SUPPLY CONTROL

INSTALLED WITH FLEXIBLE PUSH TUBING, COLOR CODED FOR APPLICATION

PUMP

STANDARD CONFIG: DARLEY 2BE21H

DARLEY 2BE 21H PUMP

MED PRESSURE, HIGH VOLUME, DIRECT DRIVE, HONDA GX 630 21HP - INSTALLED TO RISER BASE

STAINLESS STEEL WELDED PLUMBING, VICTAULIC GROOVES & COUPLINGS WHERE NECESSARY - AKRON 3" TANK-PUMP AND 2.5" SUCTION VALVES, FABRICATED VALVE STANDS, FUNCTION LABELS, ETC

TANK-PUMP LINKAGE CONTROLLED THROUGH VALVE STAND

L1/R1 TRANSVERSE

OPTION 1: 400G / 18"

TRANSVERSE OVERSLUNG CROSS FRAME L1 / R1 COMPARTMENT, NOTCHED CENTER AT 18"D TO ACCOMODATE 400 GAL POLYTANK. SWING DOOR - HINGED CAB SIDE W/ GAS SHOCK, FIXED SHELF AT THRU SECTION MIDPOINT, D RING HANDLES (BLACK)

51.5" (31.5" TOPSIDE) H X 26" (18" THRU SECTION)W X 18"/SIDE (+60" THRU SECTION) D

STRIPING / GRAPHICS

CUSTOM GRAPHICS

GRAPHICS TO BE INSTALLED PER CUSTOMER SPECIFICATIONS. PROOFS TO BE PROVIDED AND APPROVED. CUSTOM QUOTE REQUIRED [PER DEPT REQUIREMENTS].SEE PRINTS

CHASSIS FINISH

FACTORY

CHASSIS FINISH TO BE FACTORY OEM PAINT COLOR - VERMILLION RED

RADIO INSTALLATION

PREWIRE ONLY

PREINSTALL COAX ANTENNA BASE KITS W/ CONNECTOR END. MOUNT ANTENNA BASE TO CAB ROOF, INSTALL WATERPROOF CAP, ROUTE COAX TO CONSOLE, LEAVE TERMINATED POWER AND GROUND FOR FUTURE RADIO CONNECTION

TIRES

BUCKSTOP SRW: PETLAS

335/80R20 PETLAS RM910 TIRES (5) - INCLUDED WITH BUCKSTOP SRW CONVERSION KIT AS STANDARD

WHEELS

BUCKSTOP SRW CONV ALUM WHEELS

11"X20" BUCKSTOP REVERSIBLE DOT ALUM WHEELS (5)
POWDERCOATED BLACK W/ MACHINED ACCENTS

BUMPER

BUCKSTOP SRW: FORD F550 KIT BUMPER

BUCKSTOP CONVERSION KIT HEAVY DUTY BUMPER WITH BRUSH GUARD [OUTBACK]. FULL TIRE COVERAGE, WINCH MOUNTING PLATE ASSY, 6" ROUND LIGHT CUTOUTS, DITCH LIGHT CUTOUTS. POWDERCOATED HAMMER BLACK - BK62

WINCH

WARN 16.5 TI, W/ SYNTHETIC CABLE (16,500 LB)

WARN 16.5 TI 16,500 WINCH W/ SYNTHETIC CABLE INSTALLED IN BUCKSTOP FRONT BUMPER

CENTER CONSOLE

30" FORD 13.3" CONSOLE ASSY SINGLE RAD W/ PUMP CONT

HAVIS 30" FORD VSW CONSOLE: RELOCATE OEM POWER POINTS TO FACE, DUAL CUPHOLDERS, DUAL ARMRESTS, STORAGE POCKETS, ACCESSORY PLATES, & FILLER PLATES TO ACCOMMODATE SELECTIONS

SINGLE RADIO, WITH IN CAB PUMP CONTROLS (DEPT SPECIFY RADIO)

HPI MODEL 1 BODY BASE

HPI MODEL 1 BODY BASE

HPI MODEL 1 BODY BASE ASSY: ALUM REVERSED C CHANNEL FLATBED DECK, SMOOTH FRAME, SQUARE CORNER, NOTCHED FORWARD DECK CORNERS. STRAIGHT CORNER TAILBOARD W/ FULL WIDTH APRON STEP. FENDER SKIRTS, FENDER FLARES, BODY FRONT OVERLAY [ROCK GUARD], MUDFLAP KIT, DEF & DIESEL FILL KITS, DOT LIGHTING KIT, APRON HOSE BOX, L2 & R2 TOPSIDE COMPARTMENTS INCLUDED IN STANDARDIZED BODY ASSY (56"W X 31.5"H X 18"D): VERTICAL LIFT DOOR WITH DUAL GAS SHOCK, ADJUSTABLE SHELF, D RING HANDLE, COMPARTMENT CIRCLE VENT AND LOUVER ASSY.

AFT OF AXLE UNDERBODY

GUSSET ASSEMBLY (STANDARD)

3/16 ALUMINUM GUSSETED REAR FLATBED UNDERBODY AFT OF AXLE ENCLOSURE KIT. DOUBLE ANGLE INWARD TO TIE FLATBED DECK TO APRON & DEFLECT FROM APRON.

TOPSIDE OVERLAY

MODEL 1 STANDARD TANK GRIP OVERLAY (400G / 500G)

TEXTURED TOPSIDE DIAMOND TREAD PLATE OVERLAY INSTALLED TO TOP OF TANK AND TRANSVERSE COMPARTMENT TO FRONT OF BODY. OVERLAY TO BE NOTCHED FOR FILL TOWERS AND TOPSIDE PLUMBING DISTRIBUTION OUTLETS. OVERLAY MOUNTS TO TANK THREADED INSERTS. INTEGRATED D RINGS SPACED FOR SPARE TIRE RETENTION.

WALKWAY TO BE POWDERCOATED PRISMATIC SUPERGRIP BLACK PTB-6419

TOPSIDE ACCESS

MODEL 1 STANDARD MODULAR STEP ASSY

ENCLOSED TOPSIDE ACCESS STEP INSTALLED OVER OFFICER SIDE DISCHARGE DISTRIBUTION AGAINST TANK & R3 COMPARTMENT. STEP NOTCHED FOR PLUMBING, VALVE CONTROLS / LINKAGES, FUNCTION CONTROLS THROUGH FACE (A/N), CUT AND FORMED .188 3003 DIAMOND PLATE TOP STEP (PRISMATIC PTB-6419), .190 5052 SIDE WALL SUPPORT (JOB COLOR)

ACCESS DOOR ON FRONT OF STEP HINGED W/ SOUTHCO C2 LATCHES TO ALLOW FOR SERVICE / STORAGE / ACCESSORY COMPONENTS

TOPSIDE TIRE MOUNT

TRIPLE LOOPS & Y STRAP TO CATWALK

STANDARD TOPSIDE SPARE TIRE RATCHETING Y STRAP, FASTEN SPARE TO TOPSIDE TANK WALKWAY D RINGS

L1/R1 TRANSVERSE ACCESSORIES

LOWER ADJUSTABLE SHELF / L1 & R1

ADJUSTABLE SHELF ADDED TO OUTER WING PORTIONS OF L1/R1 TRANSVERSE COMPARTMENT (1/ SIDE). SHELF POWDERCOATED HAMMER BLACK - BK62.

L2 OR R2 COMPARTMENT ACCESSORIES

NONE

NO ADDED ACCESSORIES TO L2 OR R2 COMPARTMENTS

REEL ENCLOSURE

NONE

NO REAR DECK HOSE REEL ENCLOSURES TO REA OF APPARATUS

BODY FINISH

POWDERCOATING - STANDARD

ENTIRE MODEL 1 BODY TO BE POWDERCOATED AS FOLLOWS:

JOB COLOR: FLATBED DECK, APRON, RAILS, COMPARTMENTS INSIDE & OUTSIDE, HEX PUNCH GUARDS, ETC

BLACK BK62: SHELVES, ACCESSORY COMPONENT, STEPS, FENDER FLARES, TOPSIDE COFFIN BOXES, TOPSIDE BASKETS, DOOR HANDLES, CROSSFRAME ROCK GUARD, ETC

BACK UP CAM

INSTALL FACTORY CAM TO BODY / WIRE TO DISPLAY

FACTORY SUPPLIED BACK UP CAMERA TO BE PLACED AT REAR OF BODY AND INTEGRATED TO HEAD UNIT WITH OEM PROVIDED COMPONENTS AND WIRING HARNESS.

CAB STEPS

FACTORY

FACTORY CAB STEPS TO BE UTILIZED.

BODY SIDE STEPS

BODY - SIDE ZICO (EA SIDE)

(2) ZICO PS-8 MANUAL PULL OUT STEPS INSTALLED UNDER L1 & R1 AT REAR BOTTOM EDGE, TO ACCESS TOPSIDE DISCHARGES OR CARGO

BATT CHARGER

KUSSMAUL CHIEF 4012

KUSSMAUL CHIEF SERIES BATTERY CHARGER W/ BUILT IN TOUCH DIISPLAY AND COMMUNICATIONS. IP32 RATED, PLC LOAD COMPENSATION BUILT IN. CHARGER MOUNTED TO INSIDE WALL OF TRANSVERSE COMPARTMENT, L1 SIDE. INPUT FROM AUTO EJECT AND OUTPUT TO BATTERY WIRING TO BE COVERED WITH Z FLANGE ALUMINUM WIRING COVER.

AUTO EJECT

KUSSMAUL CHIEF OLED, 20A, RED (4012)

KUSSMAUL 20A SUPER AUTO EJECT W/ CHIEF SERIES OLED RED COVER INSTALLED TO DRIVERS SIDE FENDER SKIRT FORWARD OF REAR AXLE. DIGITAL CHARGE INDICATOR AND STATUS CENTER INTEGRATED TO COVER. PIGTAIL WHIP TO BE PROVIDED

120V OUTLET(S) BODY - SHORELINE

NONE

NO SHORELINE POWER OUTLETS TO BE INSTALLED TO BODY

INVERTER POWER 2KW

NONE

NO FACTORY INVERTER SYSTEM

MASTER BATTERY

RED ETCHED ROCKER

STANDARD MASTER POWER SWITCH TO SUPPLY POWER TO ALL NON OEM ACCESSORIES (LESS LOADS WIRED TO CONSTANT BATTERY PER DEPT SPECIFICATIONS). ROCKER SWITCH INSTALLED TO CONSOLE WITH RED ETCHED COVER "MASTER POWER" AND STAINLESS STEEL SWITCH SHROUD GUARD.

CORE ELECTRICAL DISTRIBUTION

STANDARD

STANDARD CORE ELECTRONICS DISTRIBUTION AND POWER MANAGEMENT. CENTRALIZED AND LABELED FUSE BLOCKS, RELAYS, ELECTRICAL COMPONENT MOUNTING, SOLENOIDS, HEAVY GAUGE WIRE DISTRIBUTION AND JUNCTIONS / TERMINALS / CONNECTORS AS NEEDED TO COMPLETE.

DOOR AJAR SYSTEM

CAB & BODY DOORS, AUDIBLE + VISUAL

STANDARD DOOR AJAR: RED LIGHT AND BUZZER INSTALLED TO CENTER CONSOLE. SYSTEM TO ALERT DOOR AJAR FOR ALL BODY DOORS THROUGH COMPARTMENT LIGHTING PRESSURE SWITCH CIRCUIT AND CAB DOORS THROUGH OBDII INTEGRATION.

SCENE LIGHT SWITCHING

CAB & PUMP PANEL

SCENE LIGHT SWITCHING - ALL SCENE AND WORK LIGHTS TO BE CONTROLLED FROM PUSH BUTTONS ON CCT17 W/ CLEARLY LABELED & BACKLIT CONTROLS. TOPSIDE WORK LIGHTS, REAR SCENE LIGHTS, DRIVER BODY SCENE LIGHTS, AND OFFICER BODY SCENE LIGHTS TO BE SWITCHED FROM BOTH CAB AND AT PUMP PANEL [ON OR OFF EITHER POSITION]. PUMP PANEL SWITCHES TO HAVE ETCHED COVERS FOR FUNCTION AND BACKLIT - BOTTOM LEFT IN ROW ON PUMP PANEL.

FRONT FOG LIGHTING

BAJA DESIGNS AMBER

BAJA DESIGNS LP6 PRO AMBER RND FOG/DRIVING LIGHTS INSTALLED IN BUMPER ROUND CUTOUTS

FRONT BUMPER SCENE LIGHTING

LIGHTBAR - BAJA

BAJA DESIGNS S8 20" LED LIGHT BAR MOUNTED TO TOP OF FRONT BUMPER, CENTERED IN FRONT OF WINCH ACCESS DOOR

BODY FRONT SCENE LIGHTING

WHELEN NP6BB BODY FRONT UPPER CORNERS (EA SIDE)

(2) WHELEN NP6BB NANO PIONEER LED POD LIGHTS MOUNTED TO FRONT UPPER OUTSIDE CORNERS OF BODY [1/SIDE], ON ANGLED PEDASTAL BASE. LIGHTS DIRECTED AT DIAGONAL AWAY FROM VEHICLE

DRIVER SCENE LIGHTING

LIGHTBAR - BAJA

BAJA DESIGNS S8 20" LED LIGHT BAR MOUNTED TO LH TOPSIDE STORAGE

OFFICER SCENE LIGHTING

LIGHTBAR - BAJA

BAJA DESIGNS S8 20" LED LIGHT BAR MOUNTED TO RH TOPSIDE STORAGE

REAR WORK LIGHTING

WHELEN NP6BB UPPER REAR (DUAL)

(2) WHELEN NP6BB NANO PIONEER LED POD LIGHTS MOUNTED TO REAR UPPER BODY ON ANGLED PEDASTAL BASE. LIGHTS INBOARD OF REAR UPPER WARNING LIGHTS

TOPSIDE WORK LIGHTING

STANDARD: 5 X 9" SUNSTRIP W/SHROUD

TOPSIDE WORK / ACCESS LIGHTING - 9" FRC SUNSTRIP (5) DISTRIBUTED TO ILLUMINATE TOPSIDE OF APPARATUS AND ACCESS / WALKWAY & STEP. EXPOSED LIGHTS TO HAVE PROTECTIVE SHROUD COVER POWDERCOATED BK62.

ROCK LIGHTS

2 PER WHEEL POSITION ANGLED TO CENTER

WHITE LED ROCK LIGHTS INSTALLED TO WHEEL OPENINGS, FRONT AND BACK OF EACH TIRE - ANGLED INWARDS. 2 / OPENING (8 TOTAL) SWITCHED TOGETHER.

GROUND LIGHTING

CAB DOOR POSITIONS & 2 UNDER APRON

ROM 6" GROUND LIGHT

COMPARTMENT LIGHTING**MODEL 1 STANDARD / FRC SUNSTRIP**

FRC SUNSTRIP STANDARD COMPARTMENT LIGHTING AT DOOR THRESHOLD AS FOLLOWS

TOPSIDE LIFT DOOR COMPARTMENTS: 27" [1 / SIDE]

L1/R1 TRANSVERSE: 45" ON LH AND RH DOOR, LATCH SIDE

ADDED CENTER: 45" AT TOP OF TRANSVERSE FORWARD UPPER EDGE. 45" UNDER SHELF

ARGES SYSTEM / REMOTE LIGHT

NONE

NO WHELEN ARGES REMOTE SPOTLIGHT SYSTEM INSTALLED

SYSTEM / CONTROLLER

CENCOM CORE WCX C399 & CCTL7 21& SLIDE CONTROLLER, 3X CEM16 EXPANSION MODULES

WHELEN CENCOM CORE WECAN X CONTROL SYSTEM, CCTL7 CONTROL HEAD, AND (3) CEM16 EXPANSION MODULES - 1 UNDER HOOD FOR FRONT ELECTRONICS, 2 IN PUMP PANEL FOR REAR ELECTRONICS. DVI, V2V, VSG, WHELEN CLOUD, WECANX CAPABLE.

INTEGRATED SYSTEM TO CONTROL ALL EMERGENCY WARNING, SCENE, AND LOAD OUTPUT FUNCTIONS THROUGHOUT APPARATUS.

PROGRAMMING**STD HARNESSSES**

PROGRAMMING AND INTEGRATION TO STANDARD UNLESS OTHERWISE DISCUSSED W AGENCY

PUSH BUTTON SCENE AND WORK, TOP ROW SIREN FUNCTIONS, PROGRAM H/F MODE AND TIE TO FACTORY HORN, OBDII

INTEGRATE FOR PARK KILL FUNCTIONS VIA WHELEN SCANPORT, STD SLIDE SWITCH FLASH PATTERNS, ETC)UTILIZING J5 & J6 OUTPUTS FROM CEM16 (X3) AND DIRECT C399 CONNECTIONS. ALL REMOTE MODULES TO CONNECT TO CENCOM VIA J7 DATA HARNESSSES

LIGHT BEZEL FINISH

BLACK

ALL WARNING LIGHT SHROUDS TO BE BLACK

LIGHTBAR

WHELEN LIBERTY II WCX (FORD CHASSIS)

WHELEN LIBERTY II 54" LIGHTBAR W/ FORD F550 MOUNTING STRAP KIT. MOUNTED FRONT CAB, DUO RED / WHITE MODULES FRONT, DUO RED / AMBER MODULES REAR, RED / WHITE DUO CORNER MODULES, LEFT & RIGHT ALLEY LIGHTS, FRONT TAKEDOWNS

WHITE FUNCTIONS SWITCHED AS SCENE LIGHTS: FRONT SCENE, TAKE DOWN, L ALLEY, R ALLEY

SIREN SPEAKER

F550 GRILL MNT, SA315P

WHELEN SA315P SIREN SPEAKER INSTALLED BEHIND GRILL W/ SUPER DUTY VEHICLE SPECIFIC SPEAKER MOUNT

FRONT LOWER WARNINGS

M4 R/W DUO, CLR LENS

FRONT LOWER WARNING INSTALLED TO FRONT BUMPER, TOWARDS OUTSIDE - FORWARD FACING

WHELEN M4 SERIES RED / WHITE DUO W/ CLEAR LENS

FRONT LOWER WARNING BEZELS

M4 BLACK

BLACK FLANGE BEZEL FOR M4

FRONT GRILL WARNINGS

T SERIES R/W DUO, CLR LENS

FRONT GRILL WARNING INSTALLED TO BUMPER UPRIGHTS - FORWARD FACING

WHELEN T SERIES RED / WHITE DUO W/ CLEAR LENS

INTERSECTION WARNINGS

M2 RED, CLR LENS

INTERSECTION WARNING LIGHTS INSTALLED TO FRONT FENDER NEAR TOP OF WHEEL ARCH, FORWARD - FACING TO LEFT & RIGHT OF APPARATUS
WHELEN M2 SERIES RED W/ CLEAR LENS

INTERSECTION WARNING BEZELS

M2 BLACK
BLACK FLANGE BEZEL FOR M2

MIDSHIP WARNINGS

M2 RED, CLR LENS
MIDSHIP WARNING LIGHTS INSTALLED TO BEDRAIL CENTERED OVER WHEEL, FENDER FLARE - FACING TO LEFT & RIGHT OF APPARATUS
WHELEN M2 SERIES RED W/ CLEAR LENS

MIDSHIP WARNING BEZELS

M2 BLACK
BLACK FLANGE BEZEL FOR M2

DRIVER REAR LOWER WARNING

DS: M2 RED
WHELEN M2 SERIES LIGHTHEAD ML2RC (CLR) RED, DS REAR LOWER WARNING MOUNTED TO BEDRAIL NEAR DOT LIGHT

OFFICER REAR LOWER WARNING

OS: M2 RED
WHELEN M2 SERIES LIGHTHEAD ML2RC (CLR) RED, OS REAR LOWER WARNING MOUNTED TO BEDRAIL NEAR DOT LIGHT

REAR LOWER WARNING LIGHT BEZELS

M2 BLACK
BLACK FLANGE BEZEL FOR M2

DRIVER REAR UPPER WARNING:

DS: M6V2 RED
M6 V SERIES COMBINATION WARNING / PERIMETER LIGHT M6V2RC (CLR) RED, UPPER WARNING LIGHT, MOUNTED TO UPPER OUTSIDE BODY CORNER

OFFICER REAR UPPER WARNING:

OS: M6V2 RED
M6 V SERIES COMBINATION WARNING / PERIMETER LIGHT M6V2RC (CLR) RED, UPPER WARNING LIGHT, MOUNTED TO UPPER OUTSIDE BODY CORNER

REAR UPPER WARNING LIGHT BEZELS

M6 BLACK
BLACK FLANGE BEZEL FOR M6

SYNC MODULE

NONE
NO WHELEN VEHICLE TO VEHICLE SYNC SYSTEM

OPTICOM

LED/IR 795H
795H GTT IR OPTICOM INCLUDED AND PREINSTALLED TO LIGHTBAR CENTER. OPTICOM PROGRAMMED TO 3RD SLIDE POSITION, EMITTER PREWIRED TO TAKEDOWNS

HOWLER SYSTEM

NONE
NO WHELEN HOWLER SYSTEM

REAR TRAFFIC ADVISOR

NONE

NO REAR TRAFFIC ADVISOR INSTALLED

TRACERS - CAB

NONE

NO WHELEN TRACER CAB SIDE WARNING LIGHTS INSTALLED

POLY TANK

UPF 400 GAL - MOD 1 STD

MODEL 1 440 GALLON RECTANGULAR POLY TANK: 10 GAL INTEGRATED FOAM CELL, MOUNTING BACK, NUT INSERTS FRONT BOTT, TOPSIDE MOUNTING TAPS FOR WALKWAY

FOAM AND WATER FILL TOWERS ON DS EDGE, INLINE, WATER FILL ON TANK MIDLINE FORWARD OF FOAM CELL
UPPER RIGHT CORNER NOTCHED FOR TOPSIDE DISCHARGE OUTLETS, TANK SLEEVED FOR TOPSIDE DISTRIBUTION
59"W X 64"+2"L X 31.5" H

PRIMER

DARLEY 12V FLUIDLESS (PULL TO PRIME)

DARLEY FLUIDLESS VANE 12V PRIMER, INSTALLED UNDER BODY. PRIMER FUSED W/ 400A MEGA BOLT STYLE FUSE UNDER HOOD. PRIMER CONTROL W/ PULL STYLE HANDLE MOUNTED TO REAR BEDRAIL

PUMP PANEL BOX OPTIONS

SWEV STANDARD BOX

INTERNAL PUMP PANEL CONTROL BOX, W/ LED PANEL LIGHT, POWDERCOAT BK62

PUMP PANEL FACE OPTIONS

FACE 3: ELECTRIC ACTUATED (21H)

REMOVEABLE PANEL FACE FOR ELECTRIC ACTUATOR CONTROLS, BLACK FINISH WITH ETCHED FUNCTION LABELS

SUB PANEL BOX OPTIONS

NO EXPANSION BOX

NO PUMP CONTROL SUB PANEL BOX NECESSARY

RECIRC COOLER SYSTEM & CONTROL / FOAM CONTROL

SWEV 4 WAY PUMP COOLER AND FOAM SUPPLY SYSTEM

4 POSITION VALVE COMBINATION PUMP COOLER, FOAM SUPPLY, AND FOAM FLUSH CONTROLS. VALVE MOUNTED TO PUMP CONTROL PANEL FACE WITH POSITION ETCHED LABELING. SUPPLY RECIRCULATING PUMP COOLER MODE, MODE OFF TO FOAM SUPPLY, MODE OFF TO FOAM FLUSH, REPEAT - ELLIMINATE TANK FOAM OUT FROM ATP FOAM SYSTEM.

FRONT DISCHARGE

HEN FORESTRY MONITOR

HEN TITAL ELITE WILDLAND MONITOR INSTALLED TO FRONT BUMPER. 20GPM BLADE NOZZLE, 12V, EXTERNAL PLUMBING COUNTOUR MATCHED TO FRONT BUMPER. CONTROL JOYSTICK MOUNTED OS FRONT EDGE OF HAVIS CONSOLE ON PEDASTAL BASE. PLUMBING FROM DISTRIBUTION DC PLUMBING UNDER BODY ON OFFICER SIDE. AUTO DRAINS AT LOW POINTS FRONT & REAR. PLUMBING IN WHEEL OPENING TO BE WRAPPED IN KEVLAR SHROUD.

GROUND SWEEPS

DUAL FRONT - ELECTRIC ACTUATED - SW IND IN CAB "LEFT SWEEP, RIGHT SWEEP"

DUAL FRONT GROUND SWEEPS INSTALLED TO FRONT BUMPER. SWEEPS VALVED INDEPENDENTLY W/ ELECTRIC VALVES, SWEEP VALVE CONTROL AT HAVIS CONSOLE "LEFT SWEEP" & "RIGHT SWEEP" ETCHED ROCKER SWITCHES. IN LINE CHECK VALVES AND AUTO DRAINS TO BE INSTALLED.

PUMP FUEL SOURCE

FUEL CELL - ALUM W/ GAUGE (21H)

12GAL ALUM FUEL CELL TO SUPPLY PUMP FUEL - INCLUDES FUEL GAUGE MOUNTED TO REAR PUMP OPERATOR AREA, FUEL SUPPLY LINES AND REGULATORS A/N, CELL PC JOB COLOR

PUMP REMOTE OIL

NONE

NO PUMP REMOTE OIL KIT

WATER LEVEL GAUGE

FRC TANKVISION PRO 400 WATER

STANDARD: FRC TANKVISION PRO WATER LEVEL GAUGE (PRIMARY), TRANSDUCER, INSTALLED TO PUMP PANEL

IN CAB SLAVE WATER GAUGE

FRC TANKVISION WATER MINI

FRC TANKVISION MINI REMOTE WATER LEVEL GAUGE, INSTALLED TO HAVS CONSOLE

AUXILLARY WATER LEVEL GAUGE

FRC MAXIVISION - BODY SIDES (DUAL)

FRC MAXVISION, LARGE REMOTE WATER LEVEL GAUGE, INSTALLED TO SIDES OF BODY UPPER FORWARD DOOR FRAME (EA SIDE) L1 / R1, TIED TO VEHICLE IN PARK SIGNAL VIA SCANPORT

FOAM LEVEL GAUGE

TANK SIGHT TUBE

TANK SIGHT WINDOW ONLY - NO ADDED FOAM LEVEL GAUGE

DISCHARGE DISTRIBUTION TO TOPSIDE

SINGLE SLEEVE TO TOPSIDE OUTLETS

DISCHARGE PLUMBING SLEEVED THROUGH TANK TO FRONT CORNER OUTLET FOR CONNECTION TO TOPSIDE OUTLETS (X1)

HOSE REEL REWIND(S)

TOPSIDE DUAL: BEDRAIL/ INLINE & IN CAB

DUAL PUSH BUTTON MOMENTARY REWIND SWITCHES MOUNTED TO BEDRAIL ON EACH SIDE OF APPARATUS, INLINE WITH HOSE REELS. ETCHED BEZELS "REWIND" INSTALLED TO BOTH SWITCHES. REWIND SWITCHES ALSO INCLUDED IN CAB WITH MOMENTARY ROCKER SWITCHES AND ETCHED COVERS FOR REWIND.

HOSE REEL DISCHARGE PLUMBING

TOPSIDE DUAL - FORWARD

STAINLESS STEEL HOSE REEL DISCHARGE PLUMBING FOR DUAL TOPSIDE HOSE REELS IN "REELS FORWARD" CONFIGURATION. FROM TOPSIDE OUTLET, 1" AKRON VALVE IN REEL INLET AREA W/ ETCHED VALVE LABEL "BOOSTER REEL" ON EACH HOSE REEL.

DRIVER DECK DISCHARGE ASSY

1.5" DISCHARGE - LH REAR BEDRAIL OF PLATFORM

STANDARD 1.5" DISCHARGE ON DRIVER SIDE REAR DECK CORNER. STAINLESS STEEL PLUMBING FROM PUMP INITIAL OUTLET ASSY. 1.5" AKRON VALVE W/ ETCHED VALVE LABEL "1.5" DISCHARGE"

OFFICER DECK DISCHARGE ASSY

1.5" DISCHARGE - RH REAR BEDRAIL OF PLATFORM

AKRON 1.5" VALVE OFFICER SIDE DISCHARGE, BEZEL AND VALVE DECK STAND

OFFICER SIDE DISCHARGE DISTRIBUTION ASSY

STANDARD CORNER DISTRIBUTION

STANDARD OS CORNER DISTRIBUTION PLUMBING

DISCHARGE SUB ASSY - TANK FILL

STANDARD TANK FILL

STANDARD TANK FILL PLUMBING ASSEMBLY EXTENDING FROM OFFICER SIDE DISCHARGE DISTRIBUTION, THRU TOP OF PLUMBING STEP ALONG TANK WALL AND INTO TANK. 1.5" AKRON VALVE W/ MANUAL CONTROL. ETCHED / BENT BEZEL "TANK FILL"

MASTER DRAIN**MASTER DRAIN (STD)**

STANDARD MASTER DRAIN VALVE: INSTALLED TO BOTTOM CORNER OF REAR APRON
DRAIN ALL PLUMBING, PUMP, AND LOW POINTS

SPECIALTY / CUSTOM DISCHARGE(S)**NONE**

CUSTOM SPECIALTY DISCHARGING AS REQUIRED PER CUSTOMER SPECIFICATION

REAR CAB ORGANIZER**NONE**

NO REAR CAB ORGANIZER TO BE INSTALLED.

TOPSIDE ACCESSORIES**CUSTOM OPT-00350**

TOPSIDE RH BASKET TO HAVE HINGED REAR FACE AND PIN TO SECURE FOR DEPT STORAGE NEEDS (DEADLAY) SEE PRINTS

WINCH ACCESSORIES**NONE**

NO WINCH ACCESSORIES INCLUDED

BOOSTER HOSE**CUSTOM OPT-00439**

MATEX LIGHTWEIGHT 1" BOOSTER HOSE W/ FIELD REPLACEABLE COUPLINGS INSTALLED TO HOSE REELS 100' LENGTH EA - NH / RED

BOOSTER NOZZLE(S)**NONE**

NO PROVIDED BOOSTER NOZZLES

REAR HOSE HOOK**NONE**

NO REAR HOSE HOOKS ADDED

DRIP TORCH MOUNTS**SINGLE STATIC MNT**

SINGLE DRIP TORCH MOUNT PROVIDED AND INSTALLED (PER DEPT SPECS)

DRIP TORCHES**NONE**

NO PROVIDED DRIP TORCHES

FLASHLIGHTS - MOUNT & WIRE**NONE**

NO HANDHELD FLASHLIGHTS INCLUDED OR INSTALLED

PAC MOUNT - BOOSTER NOZZLE(S)**DUAL / PAC FLEXTMOUNT**

PAC TOOL FLEXTMOUNT INSTALLED TO EACH REEL BASE

PORTABLE RADIO CHARGERS - MOUNT & WIRE**NONE**

NO PORTABLE RADIO CHARGERS TO BE INSTALLED

SPANNER / HYD WRENCH SET (MOUNTED)

RHB TRIPLE HOLDER W/ HYD WR + 2 SPANNERS

REDHEAD WRENCH HOLDER SET WITH DUAL SPANNERS AND HYDRANT WRENCH INSTALLED PER DEPARTMENT SPECIFICATION

TOW HOOK / SHACKLE (ADDED)

2" HITCH MNT SHACKLE (FRONT BUMPER)

INCLUDE ADDED 2" REC MOUNT SHACKLE AND INSTALL TO FRONT BUMPER

WHEEL CHOCKS AND MOUNTS

AC-32W W HORIZONTAL MOUNT - PAIR

ZICO AC-32W WILDLAND COMPLIANT WHEEL CHOCK PAIR AND DUAL MOUNTS INCLUDED (SHIP LOOSE)

BULLETPoint MOUNT OPTIONS

NONE

NO AMPS 20MM BALL MOUNTS

BULLETPoint ACCESSORIES

NONE

NO BULLETPoint ACCESSORIES INCLUDED

CAB DOME LIGHTING

FACTORY

FACTORY CAB DOME LIGHTING ONLY.

ON BOARD AIR

NONE

NO ON BOARD AIR COMPRESSOR SYSTEM INSTALLED

SPITZ LIFT HOIST

NONE

NO SPITZ LIFT HOIST INCLUDED

CUSTOM: ADDED LOOSE EQUIP

CUSTOM OPT-00457

INSERT FOR ENGINEERS BOX TO BE FABRICATED AND INSTALLED TO STEP FACE / TO CREATE CUBBY IN MODULAR STEP (3/16 ALUM) W DRAINAGE

HARD SUCTION

2.5" X BODY LENGTH - NH (2)

2 SECTIONS OF 2.5" HARD SUCTION COUPLED TO BODY LENGTH AND INCLUDED, NH, PREINSTALLED TO APRON HOSE BOX, INCLUDES 2.5 BARREL STRAINER

REAR GRAB HANDLES

STANDARD (2@18")

2 STANDARD GRAB HANDLES PROVIDED AND INSTALLED TO BACK OF APPARATUS IN TOPSIDE ACCESS WALKWAY / STEP AREA AS NEEDED

HITCH STEP

SWEV FOLDING HITCH STEP SHACKLE

FABRICATED HITCH INSERT DROP STEP AND REC MOUNT SHACKLE COMBO

FLIP STEP ON DROP, 2.5" HITCH MOUNT, ACCEPTS / ADAPTS TO 2" & PRE INSTALLED W/ INCLUDED 2" HITCH SHACKLE, DOUBLE PINS, W/ INTEGRATED LIGHT WIRED TO GROUND LIGHTS ON PLUG

INTERNAL ENGINEERING

SWEV DESIGN ENGINEERING

INTERNAL DESIGN TIME AND ENGINEERING, CONCEPT DRAWINGS AND APPROVAL PRINTS, JOB SPECIFIC LAYOUT
ENGINEERING PER CONFIGURATION

PURCHASE MECHANISM

SOURCEWELL

CUSTOM ENTRY BY SALES REP REQUIRED TO COMPLETE SUBMISSION

SALES REP

CUSTOM OPT-00468

FINAL INSPECTION

FINAL INSPECTION: ON SITE @ SWEV

FINAL INSPECTION, IN SERVICE TRAINING, AND CUSTOMER ACCEPTANCE AT PRODUCTION FACILITY: YAKIMA, WA,
CUSTOMER INSPECTION COSTS NOT INCLUDED IN PURCHASE

DELIVERY

DELIVERY: AGENCY DRIVEAWAY

CUSTOMER TO DRIVEAWAY UNIT AFTER FINAL INSPECTION AND ACCEPTANCE
